


DISPLAYS

TECHNICAL INFORMATION



OPERATING VIEW MODE

In view mode the indicator displays the values of the quantities defined on the display list; it may view 1, 2 or 3 data for screen.



S401 OLED DISPLAY

The S401 is the new standard for indication with OLED display. Why use an expensive HMI when the S401 will perform many of the same functions for a lower cost.

The S401 has a very bright display of 70 cd/m² with a very high 128 x 64 pixel definition. The display also has a space saving design with dimensions of 96x48mm. It displays up to 30 measurements (float, integer, Boolean) and programming is possible via software or front key menu. Another advantage is reduced cabling with two RS485 MODBUS interfaces.

S401 DISPLAY



S401-L MODBUS RTU Display with 2.7" OLED Display, 10-40VDC, 19-28VAC, Master/Slave

Includes: 27 math functions, 20 readings from slave devices, 10 writings to slaved evices, alarm control on threshold

ENTRY LEVEL DISPLAYS



S315 Display

S315 4 Digit Loop-powered Display, 4-20mA Input, IP65

S311AK-4-L 4 Digit Display, voltage/current Input, IP65

COMPLETE DISPLAY SOLUTIONS



S311A-4-H

S311A-4-H Indicator/Totalizer with Universal Analog Input, 80-265 VAC, 4 Digit

S311A-4-H-O Indicator/Totalizer with Universal Analog Input, 80-265 VAC, 4 Digit, Optional Card



S311A-6-H-O

S311A-6-H Indicator/Totalizer with Universal Analog Input, 80-265 VAC, 6 Digit

S311A-11-H Indicator/Totalizer with Universal Analog Input, 80-265 VAC, 11 Digit

S311A-4-L Indicator/Totalizer with Universal Analog Input, 10-40VDC / 19-28VAC, 4 Digit

S311A-4-L-O Indicator/Totalizer with Universal Analog Input, 10-40VDC / 19-28VAC, 4 Digit, Opt. Card



S311D-4-H

S311A-6-L Indicator/Totalizer with Universal Analog Input, 10-40VDC / 19-28VAC, 6 Digit

S311A-11-L Indicator/Totalizer with Universal Analog Input, 10-40VDC / 19-28VAC, 11 Digit

S311D-4-H Indicator/Totalizer with Universal Digital Input, 80-265 VAC, 4 Digit

S311D-4-H-O Indicator/Totalizer with Universal Digital Input, 80-265 VAC, 4 Digit, Optional Card

S311D-4-L Indicator/Totalizer with Universal Digital Input, 10-40VDC / 19-28VAC, 4 Digit

S311D-4-L-O Indicator/Totalizer with Universal Digital Input, 10-40VDC / 19-28VAC, 4 Digit, Opt. Card

More Solutions Available - please contact us for further options