

FERRULES

GLW wire ferrules are available from 0.25mm² to 185mm² sizing with varying connection lengths. The insulated ferrules meet DIN, German and KDS colour standards and with ferrules available in single, and twin format, uninsulated and boxed reels there will be a solution for your requirement.


DIN STANDARD FERRULES

H0.25/8Y - GLW	Ferrule - 0.25mm - Length of uninsulated component 8mm - YELLOW	500
H0.5/8W - GLW	Ferrule 0.5mm - Length of uninsulated component 8mm - WHITE	100
H0.5/10W - GLW	Ferrule 0.5mm - Length of uninsulated component 10mm - WHITE	500
H0.75/10GR - GLW	Insulated Ferrule 0.75mm - Length of uninsulated component 10mm - GREY	100
H0.75/12GR - GLW	Ferrule - 0.75mm - Length of insulated component 12mm - GREY	100
H0.75/6GR - GLW	Ferrule 0.75mm - Length of uninsulated component 6mm - GREY	500
H0.75/8GR - GLW	Ferrule 0.75mm - Length of uninsulated component 8mm - GREY	100
H1.0/8R - GLW	Ferrule 1.0mm - Length of insulated component 8mm - RED	100
H1.0/10R - GLW	Ferrule 1.0mm - Length of uninsulated component 10mm - RED	100
H1.0/12R - GLW	Ferrule 1.0mm - Length of uninsulated component 12mm - RED	100
H1.5/8BL - GLW	Ferrule 1.5mm - Length of uninsulated component 8mm - BLACK	100
H2.5/8B - GLW	Ferrule 2.5mm - Length of insulated component 8mm - BLUE	100
H2.5/12B - GLW	Ferrule - 2.5mm - Length of uninsulated component 12mm - BLUE	100
H2.5/18B - GLW	Ferrule 2.5mm - Length of uninsulated component 18mm - BLUE	500
H4.0/10GR - GLW	Ferrule 4.0mm - Length of insulated component 10mm - GREY	100
H6.0/12Y - GLW	Ferrule 6.0mm - Length of uninsulated component 12mm - YELLOW	100
H10.0/12R - GLW	Ferrule - 10.0mm - Length of uninsulated component 12mm - RED	100
H10.0/18R - GLW	Ferrule 10.0mm - Length of uninsulated component 18mm - RED	100
H16.0/12B - GLW	Ferrule - 16.0mm - Length of insulated component 12mm - BLUE	100
H16.0/18B - GLW	Ferrule 16.0mm - Length of insulated component 18mm - BLUE	100
H25.0/16Y - GLW	Ferrule - 25.0mm - Length of insulated component 16mm - YELLOW	50
H35.0/16R - GLW	Ferrule 35.0mm - Length of insulated component 16mm - RED	50
H50.0/20B - GLW	Ferrule 50.0mm - Length of insulated component 20mm - BLUE	50
H95.0/25R - GLW	Ferrule 95.0mm - Length of uninsulated component 25mm - RED	25
H16.0/18B - GLW	Ferrule 16.0mm - Length of insulated component 18mm - BLUE	100
H25.0/16Y - GLW	Ferrule - 25.0mm - Length of insulated component 16mm - YELLOW	50
H35.0/16R - GLW	Ferrule 35.0mm - Length of insulated component 16mm - RED	50
H50.0/20B - GLW	Ferrule 50.0mm - Length of insulated component 20mm - BLUE	50
H95.0/25R - GLW	Ferrule 95.0mm - Length of uninsulated component 25mm - RED	25




FERRULES


GERMAN STANDARD FERRULES

	H0.25/6LB - GLW	Ferrule - 0.25mm - Length of uninsulated component 6mm - LIGHT BLUE	100
	H0.25/12LB - GLW	Ferrule 0.25mm - Length of uninsulated component 12mm - LIGHT BLUE	100
	H0.34/12T - GLW	Insulated Ferrule 0.34mm - Length of uninsulated component 12mm - TURQUOISE	100
	H0.5/8O - GLW	Ferrule - 0.50mm - Length of uninsulated component 8mm - ORANGE	100
	H0.5/10O - GLW	Ferrule 0.5mm - Length of uninsulated component 10mm - ORANGE	500
	H0.75/8W - GLW	Ferrule 0.75mm - Length of uninsulated component 8mm - WHITE	100
	H0.75/12W - GLW	Ferrule 0.75mm - Length of insulated component 12mm - WHITE	100
	H1.0/8Y - GLW	Ferrule - 1.0mm - Length of uninsulated component 8mm - YELLOW	100
	H1.0/10Y - GLW	Ferrule 1.0mm - Length of uninsulated component 10mm - YELLOW	100
	H1.0/12Y - GLW	Ferrule 1.0mm - Length of uninsulated component 12mm - YELLOW	100
	H1.5/8R - GLW	Ferrule - 1.5mm - Length of uninsulated component 8mm - RED	100
	H4.0/12GR - GLW	Ferrule 4.0mm - Length of insulated component 12mm - GREY	100
	H6.0/12BL - GLW	Ferrule 6.0mm - Length of insulated component 12mm - BLACK	100
	H10.0/12I - GLW	Ferrule - 10.0mm - Length of insulated component 12mm - IVORY	100
	H10.0/18I - GLW	Ferrule - 10.0mm - Length of uninsulated component 18mm - IVORY	100
	H16.0/12G - GLW	Ferrule - 16.0mm - Length of insulated component 12mm - GREEN	100
	H25.0/16BR - GLW	Ferrule - 25.0mm - Length of insulated component 16mm - BROWN	50
	H25.0/22BR - GLW	Ferrule - 25.0mm - Length of insulated component 22mm - BROWN	50
	H35.0/16BE - GLW	Ferrule 35.0mm - Length of insulated component 16mm - BEIGE	50
H50.0/20OL - GLW	Ferrule 50.0mm - Length of uninsulated component 20mm - OLIVE	50	
H120.0/30B - GLW	Ferrule 120.0mm - Length of uninsulated component 30mm - BLUE	25	
H150.0/32Y - GLW	Ferrule 150.0mm - Length of uninsulated component 32mm - YELLOW	25	

KDS STANDARD FERRULES












	H0.75/8LB - GLW	Ferrule - 0.75mm - Length of uninsulated component 8mm - LIGHT BLUE	100
	H0.75/12LB - GLW	Ferrule 0.75mm - Length of uninsulated component 12mm - LIGHT BLUE	100
	H2.5/8GR - GLW	Ferrule 2.5mm - Length of insulated component 8mm - GREY	100
	H4.0/10O - GLW	Ferrule 4.0mm - Length of insulated component 10mm - ORANGE	100
	H6.0/12G - GLW	Ferrule 6.0mm - Length of insulated component 12mm - GREEN	100

DIN STANDARD DOUBLE BOOTLACE FERRULES







	H2x0.5/8W - GLW	Ferrule 2x 0.5mm - Length of uninsulated component 8mm - WHITE	100
	H2x0.75/8GR - GLW	Ferrule 2x 0.75mm - Length of uninsulated component 8mm - GREY	100
	H2x0.75/12GR - GLW	Ferrule 2x 0.75mm - Length of uninsulated component 12mm - GREY	100
	H2x1.0/8R - GLW	Ferrule 2x 1.0mm - Length of uninsulated component 8mm - RED	100
	H2x1.0/12R - GLW	Ferrule 2x 1.0mm - Length of insulated component 12mm - RED	100
	H2x1.5/8BL - GLW	Ferrule 2x 1.5mm - Length of uninsulated component 8mm - BLACK	100
	H2x1.5/12BL - GLW	Ferrule 2x 1.5mm - Length of uninsulated component 12mm - BLACK	100
	H2x2.5/10B - GLW	Ferrule 2x 2.5mm - Length of uninsulated component 10mm - BLUE	100
	H2x2.5/12B - GLW	Ferrule 2x 2.5mm - Length of uninsulated component 12mm - BLUE	100
	H2x4.0/12GR - GLW	Ferrule 2x 4.0mm - Length of uninsulated component 12mm - GREY	100
	H2x16.0/16B - GLW	Ferrule 2x 16.0mm - Length of uninsulated component 16mm - BLUE	50

FERRULES

GERMAN STANDARD DOUBLE BOOTLACE FERRULES

	H2x0.5/8O - GLW	Ferrule 2x 0.5mm - Length of uninsulated component 8mm - ORANGE	100
	H2x0.75/8W - GLW	Ferrule 2x 0.75mm - Length of uninsulated component 8mm - WHITE	100
	H2x0.75/10W - GLW	Ferrule 2x 0.75mm - Length of uninsulated component 10mm - WHITE	100
	H2x1.0/8Y - GLW	Ferrule 2x 1.0mm - Length of uninsulated component 8mm - YELLOW	100
	H2x1.0/12Y - GLW	Ferrule 2x 1.0mm - Length of uninsulated component 12mm - YELLOW	100
	H2x1.5/8R - GLW	Ferrule 2x 1.5mm - Length of uninsulated component 8mm - RED	100
	H2x1.5/12R - GLW	Ferrule 2x 1.5mm - Length of uninsulated component 12mm - RED	100
	H2x2.5/10B - GLW	Ferrule 2x 2.5mm - Length of uninsulated component 10mm - BLUE	100
	H2x2.5/12B - GLW	Ferrule 2x 2.5mm - Length of uninsulated component 12mm - BLUE	100
	H2x4.0/12GR - GLW	Ferrule 2x 4.0mm - Length of uninsulated component 12mm - GREY	100
	H2x16.0/16G - GLW	Ferrule 2x 16.0mm - Length of uninsulated component 16mm - GREEN	50

KDS STANDARD DOUBLE BOOTLACE FERRULES

	H2x0.5/8W - GLW	Ferrule 2x 0.5mm - Length of uninsulated component 8mm - WHITE	100
	H2x0.75/12LB - GLW	Ferrule 2x 0.75mm - Length of uninsulated component 12mm - LIGHT BLUE	500
	H2x1.0/8R - GLW	Ferrule 2x 1.0mm - Length of uninsulated component 8mm - RED	100
	H2x1.0/12R - GLW	Ferrule 2x 1.0mm - Length of insulated component 12mm - RED	100
	H2x1.5/8BL - GLW	Ferrule 2x 1.5mm - Length of uninsulated component 8mm - BLACK	100
	H2x1.5/12BL - GLW	Ferrule 2x 1.5mm - Length of uninsulated component 12mm - BLACK	100

UNINSULATED BOOTLACE FERRULES

	H0.5/6 - GLW	Uninsulated Ferrule 0.5mm - Length 6mm	1000
	H0.75/6 - GLW	Uninsulated Ferrule 0.75mm - Length 6mm	1000
	H1.0/10 - GLW	Uninsulated Ferrule 1.0mm - Length 10mm	1000
	H1.0/6 - GLW	Uninsulated Ferrule 1.0mm - Length 6mm	1000
	H1.5/10 - GLW	Uninsulated Ferrule 1.5mm - Length 10mm	1000
	H1.5/7 - GLW	Uninsulated Ferrule 1.5mm - Length 7mm	1000
	H2.5/12 - GLW	Uninsulated Ferrule 2.5mm - Length 12mm	1000
	H2.5/7 - GLW	Uninsulated Ferrule 2.5mm - Length 7mm	1000
	H4.0/9 - GLW	Uninsulated Ferrule 4.0mm - length 9mm	1000
	H6.0/12 - GLW	Uninsulated Ferrule 6.0mm - Length 12mm	1000
	H10.0/15 - GLW	Uninsulated Ferrule 10.0mm - Length 15mm	500
	H10.0/12 - GLW	Uninsulated Ferrule 10.0mm - Length 12mm	500
	H10.0/18 - GLW	Uninsulated Ferrule 10.0mm - Length 18mm	500
	H16.0/12 - GLW	Uninsulated Ferrule 16.0mm - Length 12mm	250
	H16.0/15 - GLW	Uninsulated Ferrule 16.0mm - Length 15mm	250
	H16.0/18 - GLW	Uninsulated Ferrule 16.0mm - Length 18mm	250
	H16.0/25 - GLW	Uninsulated Ferrule 16.0mm - Length 25mm	250
	H16.0/32 - GLW	Uninsulated Ferrule 16.0mm - Length 32mm	250
	H25.0/18 - GLW	Uninsulated Ferrule 25.0mm - Length 18mm	100
	H25.0/25 - GLW	Uninsulated Ferrule 25.0mm - Length 25mm	100
	H25.0/32 - GLW	Uninsulated Ferrule 25.0mm - Length 32mm	100
	H35.0/18 - GLW	Uninsulated Ferrule 35.0mm - Length 18mm	100
	H35.0/32 - GLW	Uninsulated Ferrule 35.0mm - Length 32mm	100
	H50.0/32 - GLW	Uninsulated Ferrule 50.0mm - Length 32mm	100
	H70.0/25 - GLW	Uninsulated Ferrule 70.0mm - Length 25mm	100
	H95.0/32 - GLW	Uninsulated Ferrule 95.0mm - Length 32mm	50
	H120.0/32 - GLW	Uninsulated Ferrule 120.0mm - Length 32mm	50
	H150.0/32 - GLW	Uninsulated Ferrule 150.0mm - Length 32mm	50
	H185.0/32 - GLW	Uninsulated Ferrule 185.0mm - Length 32mm	25

FERRULES

TC MACHINE FERRULES - ROLLS



TC-H0.5/8O	TC Machine Ferrule 0.5mm ² - Length of insulated component 8mm - ORANGE	1000
TC-H0.5/8W	TC Machine Ferrule 0.5mm ² - Length of insulated component 8mm - WHITE	1000
TC-H0.75/8GR	TC Machine Ferrule 0.75mm ² - Length of insulated component 8mm - GREY	1000
TC-H0.75/8W	TC Machine Ferrule 0.75mm ² - Length of insulated component 8mm - WHITE	1000
TC-H1.0/8R	TC Machine Ferrule 1.0mm ² - Length of insulated component 8mm - RED	1000
TC-H1.0/8Y	TC Machine Ferrule 1.0mm ² - Length of insulated component 8mm - YELLOW	1000
TC-H1.5/8BL	TC Machine Ferrule 1.5mm ² - Length of insulated component 8mm - BLACK	1000
TC-H1.5/8R	TC Machine Ferrule 1.5mm ² - Length of insulated component 8mm - RED	1000

BOOTLACE FERRULE STRIPPING AND CRIMPING MACHINES



TC05	TC Automated Stripping and Crimping Machine- Hand Held Battery Operated Tool - suitable for 0.5mm ² GLW Ferrule Strips
TC07	TC Automated Stripping and Crimping Machine- Hand Held Battery Operated Tool - suitable for 0.75mm ² GLW Ferrule Strips
TC10	TC Automated Stripping and Crimping Machine- Hand Held Battery Operated Tool - suitable for 1.0mm ² GLW Ferrule Strips
TC15	TC Automated Stripping and Crimping Machine- Hand Held Battery Operated Tool - suitable for 1.5mm ² GLW Ferrule Strips