
Digital instrument available in the rear-panel version to measure direct or alternating currents.




- Normalized dimensions 72x72 mm
- 2 Reading: 14 mm 3 red digits display







Side view



Diagram

MEASUREMENT AND CONTROL

TECHNICAL INFORMATION

GENERAL CHARACTERISTICS

| Power supply | V AC | 115 / 230 (-15% ÷ +10%) | |
|-------------------------|------|-------------------------|--|
| Frequency | Hz | 50 / 60 | |
| Absorption | VA | 5 | |
| Display | | 14 mm 3 red digits | |
| View | | Max 999 | |
| Precision | | ±(0.5% f.s. + 1 digit) | |
| Front protection degree | IP | 40 | |

Compliance with Community Directives: 2006/95/EC (Low Voltage) and 2004/108/EC (E.M.C.)

is declared with reference to the following standards: • Safety: EN 61010-1 • E.M. Compatibility: EN 61000-6-2 / EN 61000-6-4

| Minimum measureable value | | 3% of the full scale |
|---------------------------|----|---------------------------------------|
| Operating temperature | °C | -10 ÷ +50 |
| Storage temperature | °C | -40 ÷ +90 |
| Terminal | | 2.5 mm ² |
| | | plug-in terminal block |
| Material | | Class VO complying with UL94 standard |
| Humidity | | 20 ÷ 90% non condensing |



DIRECT CONNECTION AC/DC AMMETERS

Measurement instruments dedicated to measure AC/DC current:

EVA-R

- Power supply: 115/230 V AC 50/60 Hz
- Minimum measureable value 3% of full scale
- Overrange indication ("HHH")

AC AMMETERS

VM321700

| Code | Model | Description | Capacity | Resolution | |
|-------------|-------|-------------|----------|------------|--|
| VM323300 | EVA-R | AC Ammeter | 1 A | 1 mA | |
| VM324100 | EVA-R | AC Ammeter | 10 A | 10 mA | |
| DC AMMETERS | | | | | |
| Code | Model | Description | Capacity | Resolution | |
| VM320900 | EVA-R | DC Ammeter | 1 A | 1 mA | |

DC Ammeter

10 A



10 mA



REFERENCE STANDARDS