

## PQI 1,5/20 BU

### 27131.5



Insulated cross-connector, No. of poles: 20, Mounting type: Plug in, Width: 69.1 mm, Colour: Blue

---

## Commercial

---

### General

---

Colour: Blue

Country of origin: DE

Customs number: 85389099

GTIN (EAN): 4044211234317

Packaging unit: 5

Product description: Insulated cross-connector

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 7.62g

Weight per piece (not including packaging): 6.8g

---

## Technical

---

### Dimensions

---

Height: 14.5mm

Length: 3.2mm

Pitch size: 3.5mm

Width: 69.1mm

### Ratings

---

Contamination degree: 3

Current load, max.: 17,5A

Max. voltage: 500V

Rated cross-section: 1.5mm<sup>2</sup>

Rated current: 17.5A

### Connection data

---

No. of poles: 20

### Further technical data

---

Insulation available: ✓

Mounting type: Plug in

Number of bridged terminals: 20

Touch protection is available: ✓

### Materials

---

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

## Approvals

---

## Environment

---

### Environmental Product Compliance

---

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

---

REACH Conform: Yes

REACH Reference date: 2026-02-04

RoHS Conform: Yes

TSCA Conform: Yes

---


## Accessories

---

### Terminal blocks



**PSL 1,5/2A GNYE**  
27001.2




**PSL 1,5/3A GNYE**  
27003.2




**PSL 1,5/4A GNYE**  
27005.2



**PRK 1,5/2A OG**  
27000.3



**PRK 1,5/3A OG**  
27002.3



**PRK 1,5/4A OG**  
27004.3

---